

AXIS Q1615 Mk III Network Camera

For premium performance with powerful processing

AXIS Q1615 Mk III combines exceptional imaging and video performance with outstanding hardware and processing capabilities including remote zoom and focus. With up to 120 fps in HDTV 1080p, it captures excellent detailed images of fast-moving objects and people. It features Axis Lightfinder 2.0 and Axis Forensic WDR for high-quality – color – images even when recorded in near darkness. Enhanced security features such as signed firmware and secure boot ensure the integrity and authenticity of the firmware. Furthermore, it includes a deep learning processing unit enabling unique opportunities to take advantage of tailor-made third-party applications based on deep learning.

- > [HDTV 1080p at up to 120 fps](#)
- > [Lightfinder 2.0 and Forensic WDR](#)
- > [TPM, FIPS 140-2 level 2 certified](#)
- > [Embedded deep learning processing unit](#)
- > [Support for third-party deep learning applications](#)



AXIS Q1615 Mk III Network Camera

| | | |
|--|---|---|
| Camera | | Wide dynamic range Video streaming indicator |
| Image sensor | 1/2.8" Progressive scan RGB CMOS | |
| Lens | Varifocal, IR corrected, CS-mount 2 MP (16:9): 2.8–8.5 mm, F1.2 Horizontal field of view: 116°–40° Vertical field of view: 61°–22° i-CS lens | |
| Day and night | Automatically removable infrared-cut filter | |
| Minimum illumination | HDTV 1080p 25/30 fps with Forensic WDR and Lightfinder: Color: 0.05 lux, B/W: 0.01 lux at 50 IRE, F1.2 HDTV 1080p 50/60 fps with Lightfinder: Color: 0.1 lux, B/W: 0.02 lux at 50 IRE, F1.2 HDTV 1080p 100/120 fps: Color: 0.2 lux, B/W: 0.04 lux at 50 IRE, F1.2 | |
| Shutter speed | 1/125000 to 2 s | |
| Video | | |
| Video compression | H.264 (MPEG-4 Part 10/AVC), Main, Baseline and High Profile H.265 (MPEG-H Part 2/HEVC) Main Profile Motion JPEG | |
| Resolution | HDTV 1080p 100/120 fps (no WDR): 1920x1080 to 160x90 HDTV 1080p 50/60 fps (no WDR): 1920x1080 to 160x90 HDTV 1080p 25/30 fps (WDR): 1920x1080 to 160x90 | |
| Frame rate | Up to 100/120 fps (50/60 Hz) in 1080p (no WDR) | |
| Video streaming | Multiple, individually configurable streams in H.264, H.265 and Motion JPEG Axis Zipstream technology in H.264 and H.265 Controllable frame rate and bandwidth VBR/ABR/MBR H.264/H.265 Video streaming indicator | |
| Image settings | Saturation, contrast, brightness, sharpness, Forensic WDR: Up to 120 dB depending on scene, white balance, day/night threshold, tone mapping, local contrast, exposure mode, exposure zones, defogging, electronic image stabilization, barrel distortion correction, compression, rotation: auto, 0°, 90°, 180°, 270° including Corridor Format, dynamic text and image overlay, polygon privacy mask, mirroring of images Scene profiles: forensic, vivid, traffic overview | |
| Pan/Tilt/Zoom | Digital PTZ, uploadable PTZ driver (Pelco D pre-installed) | |
| Audio | | |
| Audio streaming | Two-way, full duplex | |
| Audio encoding | 24bit LPCM, AAC-LC 8/16/32/44.1/48 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz, Opus 8/16/48 kHz Configurable bit rate | |
| Audio input/output | External microphone input, line input, digital input with ring power, built-in microphone (can be disabled), balanced microphone, balanced input, automatic gain control, line output 24 bit AD/DA-conversion | |
| Network | | |
| Security | Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1x (EAP-TLS) ^a network access control, digest authentication, user access log, centralized certificate management, brute force delay protection, signed firmware, secure boot, protection of cryptographic keys with FIPS 140-2 certified TPM 2.0 module | |
| Supported protocols | IPv4, IPv6 USGv6, HTTP, HTTP/2, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, Bonjour, UPnP TM , SNMPv1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SFTP, SRTP, TCP, UDP, IGMPv1/v2/v3, RTCP, ICMP, DHCPv4/v6, ARP, SOCKS, SSH, LLDP, MQTT, Syslog | |
| System integration | | |
| Application Programming Interface | Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at axis.com AXIS Guardian with One-Click Connection ONVIF [®] Profile G, ONVIF [®] Profile S and ONVIF [®] Profile T, specifications at onvif.org | |
| Onscreen controls | Electronic image stabilization Day/night shift Defogging | |
| Event conditions | Analytics, external input, supervised external input, edge storage events, virtual inputs through API Audio: audio detection Device status: above operating temperature, above or below operating temperature, below operating temperature, IP address removed, network lost, new IP address, shock detection, ring power overcurrent protection, storage failure, system ready, within operating temperature Edge storage: recording ongoing, storage disruption I/O: digital input, manual trigger, virtual input PTZ: PTZ malfunctioning, PTZ movement, PTZ preset position reached, PTZ ready Scheduled and recurring: scheduled event Video: live stream open | |
| Event actions | Record video: SD card and network share Upload of images or video clips: FTP, SFTP, HTTP, HTTPS, network share and email Pre- and post-alarm video or image buffering for recording or upload Notification: email, HTTP, HTTPS, TCP and SNMP trap PTZ: PTZ preset, start/stop guard tour Overlay text, external output activation, play audio clip, zoom preset, defog mode, PTZ control | |
| Data streaming | Event data | |
| Built-in installation aids | Focus assistant, pixel counter, leveling assistant, camera orientation aid, traffic wizard i-CS: Remote zoom and focus Other lens: Remote back focus | |
| Analytics | | |
| Compute capabilities | Deep learning processing unit (DLPU) Real-time object detection engine | |
| Applications | Included AXIS Video Motion Detection, AXIS Fence Guard, AXIS Loitering Guard, AXIS Motion Guard, active tampering alarm, audio detection Supported AXIS Perimeter Defender Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap | |
| General | | |
| Casing | Casing: Metal (zinc) Color lid: Silver RAL 9006 Color chassis: Black - NCS S 9000-N | |
| Mounting | ¼"-20 tripod screw thread Camera stand included | |
| Sustainability | PVC free, BFR/CFR free | |
| Memory | 2048 MB RAM, 1024 MB Flash | |
| Power | Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 3, max 12.95 W, typical 8.2 W 10–28 V DC, max 12.1 W, typical 8.3 W Power redundancy | |
| Connectors | Shielded RJ45 10BASE-T/100BASE-TX/1000BASE-T PoE DC input I/O: 6-pin 2.5 mm terminal block for four configurable inputs/outputs (12 V DC output, max load 50 mA). Two of the ports can be supervised. RS485/RS422, 2 pcs, 2 pos, full duplex, terminal block 3.5 mm mic/line in, 3.5 mm line out i-CS connector (compatible with P-Iris and DC-iris) AXIS T92G20 connector | |
| Storage | Support for microSD/microSDHC/microSDXC card Support for SD card encryption (AES-XTS-Plain64 256bit) Recording to network-attached storage (NAS) For SD card and NAS recommendations see axis.com | |
| Operating conditions | -10 °C to 55 °C (14 °F to 131 °F) Humidity 10–85% RH (non-condensing) | |

| | | |
|-----------------------------|--|---|
| Storage conditions | -40 °C to 65 °C (-40 °F to 149 °F) Humidity 5-95% RH (non-condensing) | Lens i-CS 9-50 mm F1.5 8 MP Ricom 2 MP Lens DC-iris 8-26 mm F0.9 |
| Approvals | EMC EN 55032 Class A, EN 61000-3-2, EN 61000-3-3, EN 55024, EN 55035, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-3(A)/NMB-3(A), VCCI Class A, RCM AS/NZS CISPR 32 Class A, EAC, KCC KN32 Class A, KN35 Safety IEC/EN/UL 62368-1 Environment IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78 Network NIST SP500-267 | Optional accessories Axis mounts, Axis lenses, Axis midspans, Axis microphones AXIS T92G20 Outdoor Housing AXIS T92E20 Outdoor Housing AXIS T8355 Digital Microphone For more accessories, see axis.com |
| Dimensions | 82 x 58 x 195 mm (3.2 x 2.3 x 7.7 in) | Video management software AXIS Companion, AXIS Camera Station, video management software from Axis Application Development Partners available at axis.com/vms |
| Weight | 1120 g (2.5 lb) | Languages English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese |
| Included accessories | Stand Connector kit, Resistorx® T20 tool, Installation Guide, Windows decoder 1-user license | Warranty 5-year warranty, see axis.com/warranty |
| Optional lenses | Lens CS 12-50 mm F1.4 P-Iris 8 MP Lens i-CS 3.9-10 mm F1.5 5 MP | a. <i>This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (openssl.org/), and cryptographic software written by Eric Young (eyay@cryptsoft.com).</i> |

Environmental responsibility:

axis.com/environmental-responsibility